

Semi-auto SMD Component Taping Machine



Features:

- 1.Track width can work freely in the range of 8mm to 72mm, the screen is easy and convenient for operate and control.
- 2.Fine adjustment head installed in hot-press device, adjustment of sealing position can accurate to $0.1\pm\text{mm}$, independent PID temperature control accurately and steadily.
- 3.The position of cover tape can make fine adjustment by adjust the tension of the moving cover tape.
- 4.Count by fiber-optical sensitive and equipped with leakage detection make braiding accurate.
- 5.Moving tape speed can be adjusted continuously and control by pedal, Ccompatible with all ELA-481 standard plastic reels.

Specifications:

Model	SM-1000A	SM-1000B	SM-1000C
Mchine Dimension:	1650*460*580mm (L*H*W)	1650*460*580mm (L*H*W)	2180*460*580mm (L*H*W)
Difference	Normal model	With pocket detecte function	Long length model
Feeding:	suitable with ELA-481 standard wheel and cover tape		
Tape width	12mm-72mm (8mm need customized)		
Power supply:	AC200V50HZ		
Pressure:	3.0kg/cm ²		
Temperature control:	two heads and independent PID temperature control, temperature range is 20-200°C		
Taping speed:	3000-7000PCS/hr. According to specific Component		
Calculator:	count by fiber-optical sensitive		
Package type:	self adhesive or hot sealing		
Weight:	50KG	50KG	70KG

Detail Pictures



Package

